



PART NUMBER SPECIFICATIONS

Go through the eleven blocks of options listed below and select an option code for each specific feature you need.

Option >	A	B	C	D	E	F	G	H	I	J	-	K*
Part Number >											-	

OPTION	CODE	FEATURES					
A Product Type	1	Pressure Gauges					
	2	Sea Water (Pneumo) Depth Gauges					
	3	Caisson Gauges (8½" and 6" dial sizes only)					
B Accuracy	0	¼% Full Scale (Calibration Certification included)					
	1	½% Full Scale					
	2	½% Mid-Scale, 1% Full Scale					
C Dial Size	0	6"					
	1	4½"					
	2	3½"					
	3	2½"					
	4	2" (minimums apply)					
	8	8½"					
D Case Type	F	Front Flange (8½", 6", 4½" and 2½" only)					
	M	No Flange Metal (4½" only; Flange Kit available)					
	N	No Flange (6", 4½", 2½" and 2" only)					
	R	Rear Flange (6", 4½" and 2½" only)					
	S	No Flange Stainless Steel (4½" only; Flange Kit available)					
	T	Turret (3½" and 4½")					
E Pointer Type	I	Process (bold, easy-reading)					
	T	Test (knife-edged, precision reading)					
F Dial Trim		Dial Size	Mirror Band	Pointer Dampening	External Zero Adjust	Material*	
	A	2½", 4½", 6", 8½"	No	No	Yes	Stainless	
	B	2½", 4½", 6", 8½"	No	Yes	Yes	Stainless	
	D	All Sizes	No	Yes	No	Stainless	
	M	2½", 4½", 6", 8½"	Yes	Yes	Yes	Stainless	
	N	All Sizes	No	No	No	Stainless	
	R	Obsolete (same as "D")					
	S	Obsolete (same as "N")					
	W	2½", 4½", 6", 8½"	Yes	No	Yes	Stainless	
	*NOTE: All 2" dials are aluminum.						
G Pressure Range	XX	A two character code specifies pressure range and units of measurement. See Dial Availability Chart for available ranges and their corresponding codes.					



H Case Color	CODE	Color	Available Case Types/ Sizes (limitations apply)	
	A	Black	All case types and sizes	
	B	Blue	All case types except 3½" Turret	
	G	Green	4½" & 6" Front, No, Rear Flange/ 8½" Front Flange	
	H	High-Temp Yellow (Glass-filled nylon)	4½" Turret Only	
	R	Red	All case types except 3½" Turret	
	U	Unpainted	Metal, Aluminum and SS cases only	
	W	White	4½" & 6" Front, No, Rear Flange/ 8½" Front Flange	
	X	Customer Specified (min. quantities may apply)	Contact the Factory	
	Y	Yellow	All case types except 3½" Turret	
I Fitting Position	0	Rear		
	2	Bottom (6 o'clock position)		
	4	Top (12 o'clock position)		
J Fitting Type	1	¼ NPT	6	AS5202004 (MS33649-04)
	2	Not Assigned	7	Not Assigned
	3	½ NPT	8	9/16-18 O-ring union (MIL-G-18997)
	4	AS33514E04 (MS33514E04)	9	¼ BSP
	5	AS4395E04 (MS33656E04)	X	Customer Specified (VCR style, etc.)
K Miscellaneous Options * there is no limit to the number of options you may select	C	Calibration certificate (included with all test gauges)		
	E	EPDM isolator installed		
	H	Helium leak test certified		
	L	Tempered glass lens		
	N	Microbraze		
	O	Oxygen cleaned		
	P	Stop pin		
	R	Reid vapor handle		
	T	Stainless steel tag		
	V	Viton® isolator installed		
	Z	Aluminum case (2½" No Flange, 3½", 4½" & 8½" Rear Flange case types only)		